

BT12 12-lead ECG

Fast, accurate 12-lead ECG waveform data capture for easy integration to your telehealth solution.

The Vitalograph BT12 ECG rapidly turns your mobile phone, tablet, or PC into a powerful electrocardiograph.



Technical Specifications

Product:	BT12 ECG Model 4130
Model:	4130
Dimensions:	6.1cm x 10.6cm x 2.3cm
Weight, including cable:	210 g incl. batteries (154 g without batteries)
Power Supply:	2 * AA batteries (1.5 V) or rechargeable batteries (1.2 V)
Data transmission:	Wireless, standard Bluetooth 2.1
EMC Standards:	EN60601-1-2007
Electrodes:	Standard clip ECG electrodes
Signal output:	Missing signal/connection termination Electrode loss
Sample Rate:	500Hz
Digital Resolution:	2.6 μ V
Bandwidth:	0.05 HZ – 150 Hz digital
Lead Configuration:	10 lead Patient cable/ 12 lead ECG
Screen Display:	LCD
Range:	Approximately 10 metres
Bluetooth Technology:	Serial transmission protocol with SDP
Runtime:	9 to 13 hours of operation depending on the type of batteries used.
Defibrillation Protection:	Yes (With supplied Cable)

Vitalograph® and Vitalograph® are trademarks or registered trademarks of Vitalograph Ltd. The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Vitalograph is under license. All other trademarks and trade names are those of their respective owners.

BT12 12-lead ECG



Technical Specifications (continued)

Pacemaker Detection:	Yes
Resolution:	24 bit A/D converter (15 bit transmitted)
Degree of protection against penetration of water:	IPX3
Operating Temperature Range:	0 - 50°C
Operating Humidity Range:	25% - 95%
Air pressure range:	700hPa - 1060hPa
Current consumption at 3 V - Operation - Stand-by	148 mA (BT12) 37 mA (BT12)
Intermediate data memory (data saving mode):	Is sufficient for at least 6 minutes of ECG
Classification in acc. with 60601-1 Type of protection against electric shock: Degree of protection against electric shock:	Device with internal power supply Type BF
Sound pressure level of signal regulated over 5 levels:	37 dB – 55 dB
Wireless transmission:	Approved in accordance to R&TTE directive transmitter module marked by CE, manufactured by MITSUMI incorporated to OEM product.
Product class in acc. with 93/42/EWG (MDD):	Ila

Provided By:

 TECHNOLOGY OF THE FUTURE, TODAY™
 866-624-3952
www.thinkMDI.net

Vitalograph® and Vitalograph® are trademarks or registered trademarks of Vitalograph Ltd. The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Vitalograph is under license. All other trademarks and trade names are those of their respective owners.